



ZPXK2.E308252 Wiring, Printed - Flexible Material Constructions - Component

For enhanced search functionality, please visit UL's [iQ™ Family of Databases](#).

Click on a product designation for complete information.

[Page Bottom](#)

Wiring, Printed - Flexible Material Constructions - Component

[See General Information for Wiring, Printed - Flexible Material Constructions - Component](#)

SUIWA HIGH TECHNOLOGY ELECTRONIC INDUSTRIES (XIAMEN) CO LTD

E308252

1776 LVLING RD

XIAMEN, FUJIAN 361009 CHINA

	Cond Width				Max			Max			
	Min	Cond	SS/			Area	Solder				
	Min	Edge	Thk	DS/	Diam	Limits		Temp	Flame	UL796	T
Type	mm(in)	mm(in)	mic(mil)	DSO	mm(in)	C	sec	C	Class	DSR	I
Multilayer flexible materials interconnect constructions, Flammability Recognition only.											
SW-15	-	-	-	DS	-	275	10	-	V-0	-	-
SW-16	-	-	-	DS	-	280	10	-	V-0	-	-
SW-2	-	-	-	DS	-	260	10	-	V-0	-	-
Multilayer Rigid Flex Composite, Flexible Materials Interconnect Constructions (Flex-to-Install Application).											
SW-11	0.07 (0.003)	0.07 (0.003)	12 (0.47) Int:17	DS	25.4 (1.0)	280	10	105	V-0	-	-
Single Layer (product may differ based on construction) Flexible Materials Interconnect Constructions (FMIC) for use in Rigid-Flexible Constructions..											
SW-10	0.07 (0.003)	0.07 (0.003)	17 (0.67)	DS	25.4 (1.0)	280	10	105	V-0	-	-
SW-13	0.09 (0.004)	0.09 (0.004)	14 (0.55)	DS	25.4 (1.0)	280	10	105	V-0	-	-
SW-17	0.05 (0.002)	0.05 (0.002)	9 (0.35)	DS	25.4 (1.0)	280	10	105	V-0	▲	-
SW-18	0.05 (0.002)	0.05 (0.002)	9 (0.35)	SS	25.4 (1.0)	280	10	105	V-0	All	-
Single layer Flex-to-Install, Flexible Materials Interconnect Constructions..											
SW-9	0.07 (0.003)	0.07 (0.003)	12 (0.47)	DS	25.4 (1.0)	280	10	105	V-0	All	-
Single layer flexible materials interconnect constructions, Flammability Recognition only.											
S1	-	-	-	DS	-	280	10	-	V-0	-	-
SW-1	-	-	-	DS	-	260	10	-	V-0	-	-
SW-12	-	-	-	DS	-	280	10	-	V-0	-	-
SW-3	-	-	-	DS	-	280	10	-	VTM-0	-	-

Marking: Company name or tradename "SUIWA" , "SW" , "suiwa" or trademark or file number and type designation. May be followed by a suffix to denote factory identification or burning test classification.

Last Updated on 2014-09-27

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

◆ 2015 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2015 UL LLC".